



SINCE 1962
Coated Abrasives Conversion Equipment
made in Switzerland

Continuously working tape applicator type 494-FAS



Continuously working tape applicator
type 494-FAS

- » Tape widths up to 25 mm
- » Automatic gluing and coating system
- » Drying of the tape with two drying elements
- » Flush-cut possible
- » Cutting angle is adjustable
- » Adhesive container in different sizes available
- » Extension of inserting stretch for wide belts (approx. 1500 mm)
- » Working direction from right to left (standard)
- » Designed for joint direction AL
- » For narrow belts and wide belts



Cutting head


Tape applicator type FAS

- The tape is automatically applied on the lap end after the lap is glued and dried to guarantee an immediate adhesion.
- The cutting angle is adjustable, so that all common joint angles can be prepared.
- The tape can be cut flush with the belt edge or in order to facilitate the positioning in the press a piece of the tape may protrude.
- The machine works with a fixed speed to allow a time-controlled cut.

General information

- Machine frame with two-speed drive (approx. 0.1 m/sec and 0.2 m/sec).
- Two steel feet for a working height of approx. 1020 mm.
- Compressed air of 6 bar.
- Standard electric supply 400 V - 3 ph - 50 Hz.

Joint directions



Joint directions type AL and AR (seen from the grain side).
Recommended: type AL



Tape coater with adhesive container